



## Product information

# SYNTEKO SOAP 1617

## GENERAL DESCRIPTION

Synteko Soap is suitable to be used after treatment of wooden floors with Synteko Solid 1612 and Synteko Belle 1614. The product can also be used for cleaning and maintenance of natural wood. It is also possible to use the product on surfaces treated with floor finishes and also on ceramic or natural stone floors.

## TECHNICAL DATA

<b>Base material</b>	Yellow potash soap based on coconut/soy-oil derivatives and complex forming agents
<b>Viscosity</b>	Low viscous liquid
<b>pH</b>	Alkaline
<b>Flash point</b>	> +100°C
<b>Shelf life</b>	36 months in unopened container
<b>Storage</b>	Store frost-free. Must be stored between +5°C (+40°F) and +30°C (+86°F)

## DIRECTIONS FOR USE

### Hardwood floors treated with Synteko Solid 1612, Synteko Belle 1614.

When necessary, for regular cleaning, but not earlier than one week after oil treatment, floors may be washed with a 1 to 20 dilution of Synteko Soap in lukewarm water, using a well wrung cloth.

## HEALTH & SAFETY INFORMATION

Keep out of reach of children. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet).



Akzo Nobel Decorative Coatings AB  
Synteko Floor Finishes  
SE-205 17 Malmö, Sweden  
Phone: +46 40 355000  
www.synteko.com  
Email: info@synteko.com



*Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.*

*Date: 2005-09-29*