

SYNTEKO RE-COVER



1620

Synteko RE-COVER is a maintenance oil for periodic maintenance of hardwood and cork floors treated with Synteko floor oils

AREA OF USE: for periodic maintenance

PRODUCT PROPERTIES:

- oxygen curing
- faintly smelling
- ready to use
- non-yellowing

COVERAGE:

- 50-100 m²/l, depending on tools and wood species

TOOLS:

- rubber spatula, 300-500 mm width or non-flocculent floor cloth for application
- non-flocculent floor cloth for polishing
- clean tools with white spirit (UK)/mineral spirits (USA)

TECHNICAL DATA:

Base material	Alkyd ester
Solids content	Approx. 77%
Solvent	Aromatic free white spirit (UK) / mineral spirit (USA)
Density	Approx. 910 kg/m ³ (8,64 lbs./gal US) (10,37 lb/gal UK)
Fire hazards	Flammable. Flash point +40°C (104°F)
Time for application	It is recommended to wait about 3 hours after the last application before the final buffing is made
Drying time	Approx. 2-4 hours
Storage	Store frost-free. Must be stored between +5°C (+50°F) and +30°C (+86°F)
Self life	24 months in unopened container from production date (s. package)
Package size	1L

BEFORE USING THE FLOOR

- Do not use vapour-proof, non-skid underlays or other coverings
- Attach felt pads to the legs of chairs and tables in order to avoid scratching the finish.

ATTENTION!

- Vacuum or dry-mop floors regularly
- Be sure to start regular maintenance before the surface is worn through to bare wood.

SYNTEKO RE-COVER DIRECTIONS FOR USE



For periodic maintenance of floors treated with Synteko oils use **Synteko Re-Cover 1620**. How often you use it will depend on the amount of traffic and how often the floor is cleaned:

- normally every other year for residential areas
- approx. 2–4 times per year for commercial areas.

Regular maintenance will restore the lustre of the floor and keep it looking beautiful.

Be sure to begin regular maintenance before you wear through to the bare wood. You can also use Re-Cover for local repairing.

Clean the floor with a Synteko Remover (s. separate Product Information) solution. Make sure the floor is completely dry before applying Synteko Re-Cover.

Apply it thinly with a rubber spatula, floor cloth or similar. Allow the floor to absorb the Re-Cover for 10–15 minutes before applying it again (if necessary).

Let the surface dry for 20 minutes and polish the floor with a clean, dry, non-flocculent floor cloth. The floor may be used after 2–4 hours.

Read also separate product information for Re-Cover 1620.

HEALTH & SAFETY INFORMATION

Safety data sheet available for professional user on request. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet) www.synteko.com. The following only represents a selection of important information.

Note: Flammable. Do not breath vapour and spray mist. Contains drying oil.

RISK OF SELFIGNITION! CONTAINS DRYING OIL. COLLECT AND KEEP SPILLAGES, USED RAGS ETC IN FIREPROOF CONTAINER AND DESTRICT.

Contains: Butanone oxime (2-) May produce an allergic reaction. Keep out of reach of children.

Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.



Producer:
Akzo Nobel, Estonia
www.synteko.com

Date: 04.03.2010

